

# TE-S TRASMISSIONI ELASTICHE A PIOLI CON SUPPORTO / PINS ELASTIC TRANSMISSIONS WITH SUPPORT

Giunto standard: ghisa UNI EN 1561 EN-GJL-HB 200  
 Standard coupling: cast iron UNI EN 1561 EN-GJL-HB 200  
 Perni standard: acciaio zincato  
 Standard pivot: galvanized steel  
 Piolo in gomma: Shore 75-80 temperatura di esercizio -20° +80°  
 Rubber pin: Shore 75-80 operating temperature -20° +80°  
 Flange: acciaio UNI EN 10277-2-C45  
 Flange steel: UNI EN 10277-2-C45  
 Allunga centrale: acciaio UNI EN 10305-1-E235+A  
 Central spacer steel: steel UNI EN 10305-1-E235+A



A richiesta trasmissione completamente in C45 o INOX  
 Coupling completely made of C45 or stainless steel upon request

| TIPO<br>TYPE | Mt<br>torque<br>[Nm]<br>max. | Ø<br>grezzo/max.<br>raw/max.<br>[mm] | F<br>[mm] | L<br>[mm]                   | L1<br>[mm]                  | H<br>[mm] | K<br>[mm] | M<br>[mm] | S<br>[mm] | N°<br>perni<br>corti<br>short<br>Pivot | N°<br>perni<br>lungi<br>long<br>Pivot | Ø<br>Perni<br>Pivot |
|--------------|------------------------------|--------------------------------------|-----------|-----------------------------|-----------------------------|-----------|-----------|-----------|-----------|--|---------------------------------------|---------------------|
| TE-S160      | 900                          | - / 60                               | 160       | A richiesta<br>Upon request | A richiesta<br>Upon request | 3         | 20        | 102       | 90        | 16                                     | 16                                    | 8XM8                |
| TE-S180      | 1300                         | - / 65                               | 180       |                             |                             | 4         | 25        | 103       | 100       | 12                                     | 12                                    | 12XM12              |
| TE-S200      | 1800                         | - / 75                               | 200       |                             |                             | 4         | 25        | 118       | 115       | 14                                     | 14                                    | 12XM12              |
| TE-S225      | 2600                         | 40 / 90                              | 225       |                             |                             | 4         | 25        | 145       | 130       | 16                                     | 16                                    | 12XM12              |
| TE-S250      | 4600                         | 45 / 95                              | 250       |                             |                             | 5         | 38        | 147       | 150       | 14                                     | 14                                    | 18XM18              |
| TE-S300      | 6500                         | 50 / 110                             | 300       |                             |                             | 5         | 38        | 182       | 180       | 16                                     | 16                                    | 18XM18              |
| TE-S350      | 10500                        | 60 / 120                             | 350       |                             |                             | 6         | 60        | 200       | 200       | 12                                     | 12                                    | 25XM24              |
| TE-S400      | 14500                        | 70 / 140                             | 400       |                             |                             | 6         | 60        | 232       | 220       | 14                                     | 14                                    | 25XM24              |
| TE-S450      | 21000                        | 75 / 160                             | 445       |                             |                             | 7         | 72        | 253       | 240       | 12                                     | 12                                    | 32XM30              |
| TE-S500      | 28000                        | 75 / 180                             | 495       |                             |                             | 7         | 72        | 288       | 260       | 14                                     | 14                                    | 32XM30              |
| TE-S550      | 36000                        | 75 / 210                             | 545       |                             |                             | 7         | 72        | 322       | 280       | 16                                     | 16                                    | 32XM30              |
| TE-S630      | 75000                        | 90 / 250                             | 625       |                             |                             | 7         | 90        | 375       | 280       | 14                                     | 14                                    | 45XM24              |
| TE-S680      | 95000                        | 90 / 270                             | 680       |                             |                             | 7         | 90        | 405       | 280       | 16                                     | 16                                    | 45XM24              |
| TE-S800      | 146000                       | 130 / 280                            | 795       |                             |                             | 7         | 90        | 420       | 300       | 20                                     | 20                                    | 45XM24              |
| TE-S900      | 200000                       | 130 / 300                            | 895       |                             |                             | 7         | 90        | 448       | 300       | 22                                     | 22                                    | 45XM24              |
| TE-S1100     | 300000                       | 130 / 350                            | 1100      |                             |                             | 7         | 90        | 550       | 400       | 28                                     | 28                                    | 45XM24              |

