

# TC-A TRASMISSIONI CARDANICHE / CARDAN DRIVE SHAFTS

Giunto standard: acciaio UNI EN 10277 C45 / Standard coupling: steel UNI EN 10277 C45

Flange: acciaio UNI EN 10277 C45 / Flange: steel UNI EN 10277 C45

Profilo scanalato: DIN5480 / Spline DIN 5480



TIPO TYPE	Mt Torque [Nm]	$\alpha^\circ$	$\varnothing$ max. max. [mm]	F [mm]	F1 rotazione rotary [mm]	M [mm]	S [mm]	S1 [mm]	H [mm]	H1 [mm]	L [mm]	Escursione Range [mm]	N° fori flange esterne Quantity external flanges holes [n°]	$\varnothing$ fori flange esterne Ø of external flange holes [mm]
TC-A 1	190	30/25	20/25	58/65	65/65	32/40	30/40	30/30	3,5/4	3,5/4	A richiesta-Upon request	A richiesta-Upon request	4/4	5/6
TC-A 2	400	30/20	25/30	65/75	73/73	40/45	40/48	32/32	4/5,5	4/5,5	A richiesta-Upon request	A richiesta-Upon request	4/6	6/6
TC-A 3	920	30/18	30/35	75/90	70/70	45/52	48/55	36/36	5,5/6	5,5/6	A richiesta-Upon request	A richiesta-Upon request	6/4	6/8
TC-A 4	1700	20/18/35	35/40/35	90/100/90	86/86/86	52/60/52	55/62/55	42/42/52	6/7/6	6/7/6	A richiesta-Upon request	A richiesta-Upon request	4/6/4	8/8/8
TC-A 5	2300	20/18/35	40/55/40	100/120/100	112/112/112	60/80/60	62/70/62	46/46/58	7/8/7	7/8/7	A richiesta-Upon request	A richiesta-Upon request	6/8/6	8/8/8
TC-A 6	3350	20/18/35	55/65/55	120/150/120	125/125/125	80/95/80	85/100/85	60/60/70	8/9/8	8/9/8	A richiesta-Upon request	A richiesta-Upon request	8/8/8	8/10/8
TC-A 7	4100	20/18/35	55/65/55	120/150/120	138/138/138	80/95/80	85/100/85	60/60/72	9/9/9	9/9/9	A richiesta-Upon request	A richiesta-Upon request	8/8/8	10/10/10
TC-A 8	5500	20/20/35	65/80/65	150/180/150	145/145/145	95/118/95	115/125/115	60/60/80	10/10/10	10/10/10	A richiesta-Upon request	A richiesta-Upon request	8/8/8	12/12/12
TC-A 9	8200	20/20/35	65/80/65	150/180/150	158/158/158	95/118/95	115/125/115	75/75/90	12/12/12	12/12/12	A richiesta-Upon request	A richiesta-Upon request	8/8/8	12/14/12
TC-A 10	10000	30/30	65/80	150/180	163/163	95/118	115/125	86/86	12/12	12/12	A richiesta-Upon request	A richiesta-Upon request	12/8	12/16
TC-A 11	16850	30/30	80/110	180/225	182/182	118/165	125/170	96/96	14/15	14/15	A richiesta-Upon request	A richiesta-Upon request	10/8	16/16
TC-A 12	26750	30/30	80/110	180/225	209/209	118/165	125/180	110/110	15/15	15/15	A richiesta-Upon request	A richiesta-Upon request	10/8	16/16

