

TY GIUNTI ELASTICI A COPERTONE / TYRE ELASTIC COUPLINGS

Giunto standard: ghisa UNI EN 1561 EN-GJL-HB 200
 Standard coupling: cast iron UNI EN 1561 EN-GJL-HB 200
 Manicotto in gomma: Shore 75-80 temperatura di esercizio -20° +80°
 Elastic tyre: Shore 75-80 operating temperature -20° +80°



TIPO TYPE	Mt torque [Nm] max.	[giri/min] [RPM]	Ø grezzo/max. raw/max. [mm]	F [mm]	D [mm]	S [mm]	M [mm]	H [mm]	L [mm]	N° Perni Pivot	Ø Perni Pivot	peso weight [Kg]
TY 100	65	4500	15 / 30	80	100	18	-	20	56	8	M6	1,8
TY 130	160	4500	14 / 38	100	130	32	80	22	86	8	M6	3
TY 160	318	4000	14 / 48	125	160	38	72	30	106	10	M6	5
TY 190	487	3600	14 / 55	144	190	45	82	33	123	10	M8	7,8
TY 210	760	3100	15 / 65	167	210	51	95	41	143	12	M8	11
TY 230	1095	2880	17 / 76	188	230	57	110	42,5	156,5	12	M10	16,5
TY 250	1515	2600	17 / 85	216	250	60	124	42	162	12	M10	26
TY 275	2135	2300	17 / 90	233	275	65	135	44	174	12	M10	31
TY 310	3550	2050	21 / 102	264	310	76	152	47	199	16	M12	45,5
TY 355	5640	1800	32 / 120	311	355	90	195	11,5	191,5	20	M12	61
TY 395	9340	1600	32 / 140	345	395	102	216	8	212	20	M16	86
TY 460	16450	1500	32 / 150	398	460	115	266	28	258	24	M16	141

Da grandezza 100 a grandezza 310
 From size 100 to size 310

Da grandezza 355 a grandezza 470
 From size 355 to size 470

