

**FA GIUNTI FLESSIBILI A LAMELLE / FLEXIBLE LAMELLAE COUPLINGS**

DATI TECNICI / TECHNICAL DATA

<b>TIPO TYPE</b>	<b>Momento d'inerzia PD<sub>2</sub> PD<sub>2</sub> moment of inertia [Kgm<sup>2</sup>]</b>	<b>Rigidità torsionale Torsion stiffness [Nm/rad]</b>	<b>Coppia massima di serraggio Tightening max torque [Nm]</b>
FA95	0,0081	130.165,86	31
FA110	0,0098	348.361,05	31
FA135	0,0370	585.976,78	31
FA150	0,0640	765.681,21	31
FA186	0,1360	1.122.307,04	90
FA216	0,4880	1.588.213,38	90
FA226	0,9200	1.363.882,92	90
FA227	0,9200	2.127.259,74	90
FA250	1,2900	4.090.832,60	90
FA300	2,8700	6.349.601,22	90
FA350	5,3300	9.334.442,13	90
FA400	12,1300	13.463.830,95	90
FA450	21,3000	23.007.652,88	90
FA500	36,5000	36.409.836,79	90
FA550	60,0000	49.424.616,05	90
FA630	119,0000	101.034.849,47	300
FA680	172,0000	159.476.960,45	300
FA800	227,0000	237.105.065,61	300
FA900	285,0000	336.677.491,38	300